

HIVERTER-Si-50K

Three Phase, Multi-MPPT
Grid Tied Solar String Inverter

Key Features

- Wide DC input range
- True three phase bridge, transformerless topology
- Low sensitivity to the grid disturbance to avoid unnecessary disconnection from the grid
- Up to 3 independent MPPT to ensure optimal energy harvest
- MPPT accuracy is more than 99.9%
- Wide operating temperature range from 20°C to 60°C
- IP 65 protection for Indoor & outdoor application
- Easy to install & maintain
- DC power overloading
- User friendly interface like RS 485/Wi-Fi
- Easy to read LCD display with all operational status & necessary data as per requirement
- Reactive power controller
- Type III SPD (Surge Protection Device)
- String current monitoring
- Low Voltage Ride Through (LVRT) compliance
- Remote monitoring using a mobile based application through GPRS/Wi-Fi



Technical Specifications

No.	IEC Standard	IEC Certificate
1	Environmental Testing	IEC 60068-2 (1,2,14,30)
2	Efficiency Measurement	IEC 61683
3	Product Safety Standard	IEC 62109-1, 2
4	Grid Connectivity Standard/ Utility Interface	IEC 61727
5	Test Procedure for Islanding Prevention Measures for Utility Interconnected PV Inverters	IEC 62116 IEEE1547 IEEE1547.1
6	Electromagnet Compatibility & Electro Magnet Interference	IEC 61000-6-1 IEC 61000-6-3 IEC 61000-3-2 IEC 61000-3-3

Technical Specifications

Input (DC)	Si-50K
Recommended PV input power	55000W
Max DC power for single MPPT	22000W/16000W/16000W
Number for independent MPPT	3
Number for DC inputs	4/3/3
Max. input voltage	1000V
Start-up input voltage	350V
Rated input voltage	600V
MPPT voltage range	250V-950V
Full load DC voltage range	530V-800V
Max. input MPPT current	40A/30A/30A
Max. input current per string	12A
Max. DC input short circuit current per MPPT	48A/36A/36A
Output (AC)	
Rated power	50000W
Max. AC power	50000VA
Max. output current	80A
Nominal grid voltage	3/N/PE, 220V/380Vac, 230V/400Vac, 240/415Vac
Grid voltage range	310Vac-220Vac (According to local standard)
Nominal frequency	50/60Hz
Grid frequency range	45Hz-55Hz/54Hz-66Hz (According to local standard)
Active power adjustable range	0-100%
THDi	<3%
Power factor	1 default (adjustable ±0.8)
Performance	
Max. Efficiency up to	98.5%
European weighted efficiency up to	98.3%
Self-consumption at night	<1W
MPPT efficiency	>99.9%
Protection	
DC reverse polarity protection	Yes
DC switch	Yes
Protection class/Overvoltage category	I/III
Input/ output SPD	PV: type II standard, AC: type II
Safety protection	Anti islanding, RCMU, Ground fault monitoring
ARPC	Anti reverse power controller (optional)
Communication	
Power management unit	According to certification and request
Standard Communication mode	RS485, Wifi / Ethernet / GPRS(optional), SD card, Multi-function relay
Operation data storage	25 years
General Data	
Ambient temperature range	-25°C ~ +60°C
Topology	Transformer less
Degree of protection	IP65
Allowable relative humidity range	0-100%
Max. operating altitude	4000m
Noise	≤60dB
Weight	68kg
Cooling	Fan
Dimension (mm)	713 x737 x 297
Display	LCD display
Standard	
EMC	EN 61000-6-2, EN 61000-6-4, EN 61000-3-11, EN 61000-3-12
Safety standard	IEC62109-1/2, IEC62116, IEC61727, IEC-61683, IEC60068(1,2,14,30)
Grid standards	AS/NZS 4777, VDE V 0124-100, V 0126-1-1, VDE-AR-N 4105, BDEW, CEI 0-21/CEI 0-16, UNE 206 007-1, EN50438/EN50549, G59, EN50530, NB/T32004

Hitachi Hi-Rel Power Electronics Private Limited

Registered Office:

B-52, Corporate House, Near Judges Bunglow, Bodakdev, Ahmedabad-380054, Gujarat, India.

Manufacturing Works:

Survey # 3 & 4, Sanand GIDC II, Industrial Estate, Nr. Bol Village, Chharodi, Sanand-382110, Gujarat, India.

Authorized distributor:

Loop Solar | P: +919971136369 | E: info@loopsolar.com | W: www.loopsolar.com

In the spirit of innovation, specifications and features are subject to change without notice.



e-gallery

/hitachihirel

/company/hitachihirel

/hitachihirelindia