


ADITYA SERIES POLY

WS-300 to WS-330 (72 Cells)




- Superior Module Efficiency as per International Benchmarks**
- Positive Power Tolerance 0-5Wp**
Module binned by current
- PID Resistant with long term reliability**
- Glass with Anti Reflective Coating**
Improves light transmission


- Salt mist, Ammonia and Hail Resistant**
- Sustain Heavy Wind & Snow loads (2400 Pa & 5400 Pa)**
- IP 67 rated MC4 compatible connectors**
- Excellent Performance in low light**



I-V Curve Variation With Irradiance



I-V Curve Variation With Temperature



The specifications are for reference purpose only. Waaree reserves the right to change the specifications without prior notice.

INTERNATIONAL & NATIONAL CERTIFICATIONS



IEC 62804 | UI1703 | ROHS Compliance | REACH Compliance | INMETRO* | FIDE*

ISO 9001:2015 | ISO 14001:2004 | OHSAS 18001:2007 | IEC 61215
IEC 61730-1&2 | IEC 61701 | IEC 62716 | IEC 60068-2-68

www.waaree.com

ADITYA SERIES POLY

WS-300 to WS-330 (72 Cells)

WAAREE[®]


One with the Sun

ELECTRICAL CHARACTERISTICS

MODELS	Pmax (W)	Vmp (V)	Imp (A)	Isc (A)	Voc (V)	Module Eff. (%)
WS-300	300	36.50	8.22	8.89	45.00	15.46
WS-305	305	36.60	8.34	9.02	45.10	15.73
WS-310	310	36.70	8.45	9.14	45.20	15.98
WS-315	315	36.75	8.58	9.27	45.25	16.25
WS-320	320	36.80	8.70	9.42	45.30	16.50
WS-325	325	36.85	8.82	9.55	45.35	16.75
WS-330	330	36.90	8.95	9.65	45.50	17.01

* Mentioned electrical data are reference values which was derived at STC condition - Temp: 25°, Irradiance: 1000w/m2 and Am: 1.5Am with cleaned modules

DESIGN SPECIFICATIONS



MECHANICAL CHARACTERISTICS

Length x Width x Thickness (L x W x T) - mm	1960 x 990 x 40
Mounting Holes Pitch (Y) – mm	1060
Mounting Holes Pitch (X) – mm	942
Weight (kg)	22.5
Solar Cells per Module (Units) / Arrangement	72 / (12*6)
Solar Cell Type	Poly crystalline Silicon
Front Cover (Material / Thickness)	Tempered & Low Iron Glass, 3.2/4.0mm
Encapsulate	Ethylene Vinyl Acetate
Frame Material	Anodized Aluminum Alloy
Junction Box	IP67 rated enclosure with bypass diodes Rated voltage : 1000VDC / 1500VDC
Connector	MC4 compatible or IP67 rated
Cable	4 mm ² cross section, 1200 mm long
Fire safety class	C
Application class	A
Safety class	II
Backsheet thickness / rated voltage	≥ 300μ, 1500VDC

TEMPERATURE COEFFICIENTS AND OPERATING CONDITIONS

Temperature coefficient of Current/°C	0.0154
Temperature coefficient of Voltage/°C	-0.2775
Temperature coefficient of Power/°C	-0.3859
NOCT	46° ± 2°
Operating Temperature Range	-40° to 85°
Maximum System Voltage (IEC& UL)	1500VDC

Waaree Energies Ltd. is the flagship company of Waaree Group, and has the country's largest Solar PV Module manufacturing capacity of 1.5 GW. In addition, it is one of leading players in India in EPC services, project development, rooftop solutions, solar water pumps, and as an Independent Power Producer. Waaree has its presence in over 250+ locations nationally and 68 countries globally.

*If you need specific product certificates, and if module installations are to deviate from our guidance specified in our installation manual, please contact your local Waaree sales and technical representatives.

**Refer To Waaree's Warranty Document For Terms & Conditions

*The Specifications Are For The References Purpose Only.

Waaree Reserves The Right To Change The Specifications Without Prior Notice.

www.waaree.com